



Low Sided Vibrator Motor-Driven Vibrating Feeders

- *This is an overview of our range of feeder sizes.
- *The overall dimensions are variable and adjusted to suit specific requirements.
- *Feeder sizes not listed will be manufactured as required.
- *The listed feeders are available with deck angles from 0° to 10°.
- *For information on high sided feeders and geared exciter-driven feeders, contact Vibramech on (Tel+27 11 762 5501) or complete the website enquiry form.

Model	Pan Width (mm)	Pan Length (mm)	Overall Width (mm)	Overall Length (mm)	Overall Height (mm)	Mass (kg)	kW
PF-09-03	300	900	680	1040	510	150	2 x 0.13
PF-15-03	300	1500	850	1690	850	250	2 x 0.25
PF-20-03	300	2000	920	2190	960	290	2 x 0.25
PF-09-04	400	900	780	1040	510	170	2 x 0.25
PF-15-04	400	1500	1050	1690	715	270	2 x 0.25
PF-20-04	400	2000	1100	2210	930	310	2 x 0.4
PF-12-05	500	1200	1120	1390	820	265	2 x 0.25
PF-20-05	500	2000	1200	2210	930	460	2 x 0.6
PF-12-06	600	1200	1080	1950	950	270	2 x 0.4
PF-20-06	600	2000	1200	2210	980	520	2 x 0.85
PF-15-07	700	1500	1270	1685	845	670	2 x 0.85
PF-20-07	700	2000	1270	2190	935	890	2 x 1.1
PF-15-08	800	1500	1360	1650	790	710	2 x 0.85
PF-20-08	800	2000	1360	2190	935	900	2 x 1.1
PF-25-08	800	2500	1460	2690	1050	950	2 x 1.1
PF-30-08	800	3000	1460	3215	1200	1250	2 x 2.2
PF-20-09	900	2000	1640	2190	1010	940	2 x 1.1
PF-25-09	900	2500	1640	2690	1130	1200	2 x 1.6
PF-30-09	900	3000	1640	3215	1070	1400	2 x 2.2
PF-20-10	1000	2000	1660	2190	990	1000	2 x 1.1
PF-25-10	1000	2500	1660	2780	1270	1300	2 x 1.6
PF-30-10	1000	3000	1660	3280	1270	1450	2 x 2.2
PF-35-10	1000	3500	1660	3790	1485	1600	2 x 3
PF-20-12	1200	2000	1990	2190	1020	1100	2 x 1.1
PF-25-12	1200	2500	1990	2837	1340	1500	2 x 1.5
PF-30-12	1200	3000	1990	3247	1200	2000	2 x 3
PF-35-12	1200	3500	1990	3830	1140	2400	2 x 3.7
PF-40-12	1200	4000	1990	4260	1170	2700	2 x 3.7
PF-25-15	1500	2500	2160	2690	1130	2050	2 x 3
PF-30-15	1500	3000	2400	3270	1520	2650	2 x 3.7
PF-20-20	2000	2000	2710	2560	1655	2300	2 x 3.7
PF-30-20	2000	3000	2900	3270	1630	3100	2 x 3.7
PF-35-20	2000	3500	2900	3744	1790	3800	2 x 5.5
PF-40-20	2000	4000	3040	4270	1690	4000	2 x 7.5
PF-30-22	2200	3000	3110	3270	1640	6000	2 x 9
PF-30-25	2500	3000	3400	3300	1800	7000	2 x 11

Overall Height (mm)	Mass (kg)	kW
510	150	2 x 0.13
850	250	2 x 0.25
960	290	2 x 0.25
510	170	2 x 0.25
715	270	2 x 0.25
930	310	2 x 0.4
820	265	2 x 0.25
930	460	2 x 0.6
950	270	2 x 0.4
980	520	2 x 0.85
845	670	2 x 0.85
935	890	2 x 1.1
790	710	2 x 0.85
935	900	2 x 1.1
1050	950	2 x 1.1
1200	1250	2 x 2.2
1010	940	2 x 1.1
1130	1200	2 x 1.6
1070	1400	2 x 2.2
990	1000	2 x 1.1
1270	1300	2 x 1.6
1270	1450	2 x 2.2
1485	1600	2 x 3
1020	1100	2 x 1.1
1340	1500	2 x 1.5
1200	2000	2 x 3
1140	2400	2 x 3.7
1170	2700	2 x 3.7
1130	2050	2 x 3
1520	2650	2 x 3.7
1655	2300	2 x 3.7
1630	3100	2 x 3.7
1790	3800	2 x 5.5
1690	4000	2 x 7.5
1640	6000	2 x 9
1800	7000	2 x 11

variable and adjusted to suit specific requirements.